

Genetec Cloudlink™ 310

Cloud-managed security appliance

The Genetec Cloudlink[™] 310 is a cloud-managed appliance used to connect local network cameras to Security Center SaaS. As an IoT gateway, the 310 simplifies video management by bringing the benefits of cloud connectivity and resiliency to your physical security system. This compact appliance offers easy connection and growth; remote connectivity and configuration, with a flexible design that includes local storage.

Fit-for-need **

ideal for **8 to 32** cameras typical local retention

> 30 days

 support for
cloud or local storage



Key features

Plug and play experience

IoT gateway

Automated updates

Continuous feature delivery

Remote enrollment, configuration, and monitoring

Support for local or cloud storage

Local data buffering for enhanced resiliency

Cyber-secure by design

Benefits



Transition at your own pace – Migrate to the cloud at your own pace and tap into modern security technology without hindering your operations. Leverage existing devices, infrastructure, and systems so you can still capitalize on your past investments.



Consolidate your operations – Reduce the need for separate hardware installations to optimize cost efficiency, saving space, energy, and resources. Organizations can achieve their objectives with fewer devices, reducing upfront costs and ongoing maintenance expenses.



Ease of use – Automated update and continuous feature delivery allows you to access the latest and greatest with no effort. Never worry about compatibility and painful upgrades again.

Applications

Retail

Ideally suited for multi-site operations, the Cloudlink 310 reduces local complexity whilst significantly boosting autonomy and flexibility. It allows you to record and monitor video locally, and easily connect and manage remote sites from a centralized location.

Education

The Cloudlink 310 appliance lets you monitor entries and exits with video surveillance to protect people and assets across campus. Users can easily configure settings, manage video, and check on the status of their system from anywhere, enhancing overall situational awareness, efficiency, and scalability.

Banking

The Cloudlink 310 appliance executes workloads autonomously and can maintain uptime, even without connectivity. Take advantage of enhanced cybersecurity with automatic updates that keep your system performing smoothly at all times

Technical specifications

Processor Hexa-core, 64-bit CPU

System Memory 16 GB RAM 256 GB flash storage

Operating system Genetec Edge OS (Linux based)

Interfaces*

Primary ethernet port (WAN): 10/100/1000/2500 Mbps Secondary ethernet port (LAN): 10/100/1000 Mbps Two (2) DisplayPorts

Electrical 300W power supply, 90-264 VAC input voltage

Incoming throughput Up to 200 Mbps

Camera compatibility ONVIF Profile S

Storage

Storage options Standard retention: 8 TB raw (7.4 TB usable). Extended retention: 20 TB raw (19.3 TB usable).

Standard retention model** 30 days of local storage for 8 Full HD at average scene activity, H.264, 15 fps video streams

Extended retention model** 30 days of local storage for 32 Full HD at low scene activity, H.264, 15 fps video streams

Mechanical and environmental

Dimensions (W x D x H) Small form factor 3.7" x 11.5" x 11.4" (97 mm × 292 mm × 290 mm)

Weight 11.4 lbs (5.1 kg)

Operating temperature 41°F to 113°F (5°C to 45°C)

Operating humidity 20% - 80% (Operating)

5% - 95% (Storage)

NDAA compliant

Certifications Regulatory IEC 60950-1, European Norm EN 60950-1, CISPR 22/CISPR 24, EN55022/55024

Cybersecurity

Encryption methods

Encryption of data in-transit using TLS 1.2 Encryption of data at rest using AES-256

Cyber-secure appliance Secure Boot Cyber-hardened Genetec Edge OS leveraging hardware TPM (Trusted Platform Module)

Warranty and support

Hardware warranty 3-year warranty

Compatible solution Security Center SaaS

Genetec Inc. genetec.com/locations info@genetec.com @genetec *Hardware specifications are subject to change. Units provided will be equivalent or superior to what is shown in this document. Display ports: refer to admin guide for uses supported. **Refer to https://svcalculator.genetec.com/ for more simulations.

© Genetec Inc., 2024. Genetec, Streamvault and the Genetec Logo are trademarks of Genetec Inc., and may be registered or pending registration in several jurisdictions. Other trademarks used in this document may be trademarks of the manufacturers or vendors of the respective products.